

# 600 CBR Series Contemporary RO Faucet



## Features:

- Retrofits most brands
- Smooth operating ceramic disk element
- Lever style handle
- High reach neck design of 12" (305 mm)
- Neck swivels 360°
- Protective spout tip prevents after drip
- Patented modular air gap (U.S. patent #7,011,106)
- Base diameter is 2-1/4" (57 mm)
- Two year warranty
- Spout reach is approximately 5" (127 mm)
- Pressure rating: 125 PSI/8.6 BAR
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI/2.32 BAR
- Temperature rating: 40°F/4°C to 150°F/66°C
- 1/4" OD x 30" tubing pre-installed
- Includes installation hardware and instructions

## Codes Applicable:

●The 600 PBR Series Contemporary RO Faucet is certified to NSF/ANSI Standard 61 – Annex G. These Contemporary RO Faucets are low-lead plumbing products and are in compliance with California's Health and Safety Code (Section 116875; commonly known as AB1953).

- ADA Compliance - ANSI A117.1

## Colors/Finishes:

- Polished chrome (#1020587)
- Satin nickel (#1020889)
- White (#1020893)
- Biscuit (#1020897)
- Polished brass (#1020895)
- Antique bronze (#1020891)
- Black (#1020894)
- Bright nickel (#1020892)
- Brushed Stainless (#1020896)

## Common Replacement Parts:

- Cartridge (#1917362)

Technical dimensions on reverse side.

Technical dimensions on reverse side.

[www.tomlinsonind.com](http://www.tomlinsonind.com)



