



UNIVAR

Univar USA Inc.
17425 NE Union Hill Road
Redmond, WA 98052
(425) 889-3400

For Emergency Assistance involving chemicals call - CHEMTREC (800) 424-9300

=====

The Version Date and Number for this MSDS is : 09/11/2007 - #022

PRODUCT NAME: LIQUICHLOR/SODIUM HYPOCHLORITE 9-16%

MSDS NUMBER: OX622680

DATE ISSUED: 09/11/2007

SUPERSEDES: 01/23/2006

ISSUED BY: 008546

MATERIAL SAFETY DATA SHEET

SECTION I IDENTIFICATION

Distribution:

UNIVAR USA
17425 NE Union Hill Road
Redmond, WA 98052
425-889-3400

TRADE NAME: LIQUICHLOR/SODIUM HYPOCHLORITE 9-16%

CHEMICAL NAME: Sodium Hypochlorite

FORMULA: NaOCl

DOT SHIPPING NAME: Hypochlorite Solution

DOT HAZARD CLASS: 8

UN/NA NUMBER: UN 1791

DOT LABEL: Corrosive

DOT PLACARD: Corrosive

PACKING GROUP: III

REPORTABLE QUANTITY: Sodium Hypochlorite: 100 Pounds/45.4 Kilograms

CAS NUMBER: 7681-52-9

NFPA DESIGNATION: Health 3 Fire 0 Reactivity 1

HMIS DESIGNATION: Health 3 Fire 0 Reactivity 1

SECTION II - HAZARDOUS INGREDIENTS

MATERIAL	% BY	CAS NO.	OSHA	ACGIH
----------	------	---------	------	-------

	WEIGHT		PEL	TLV
Sodium Hypochlorite	9-16	7681-52-9	N/A	N/A
Sodium Hydroxide	0.1-2.0	1310-73-2	2mg/m3 ceiling	2mWm3 STEL /CEIL(c) ceiling
Inert Ingredients	Balance	N/A	N/A	N/A

CARCINOGENICITY STATUS: NTP - No, IARC - No, OSHA - No.

SECTION III - PHYSICAL DATA

APPEARANCE: Yellow-green liquid
 BOILING POINT: 219 deg F (104 deg C) for 12.5% NaOCl by wt.
 FREEZING POINT: - 11 deg F (- 24 deg C) for 12.5% NaOCl by wt.
 ODOR: Chlorine
 pH: 12.5 - 13.5 s.u. @ 25 deg C
 VISCOSITY (Cs): 2.15 @ 23 deg C for 12.5% NaOCl by wt.
 % VOLATILE BY VOLUME: Variable water plus products of decomposition
 SOLUBILITY IN WATER: Complete
 SPECIFIC GRAVITY (Water----1): 1.196 @ 20 deg C for 12.5% NaOCl by wt.
 VAPOR DENSITY (AIR=1): Not available
 VAPOR PRESSURE (mm Hg): Variable water plus products of decomposition

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (Test method): Not applicable

AUTO IGNITION TEMPERATURE: Not applicable

FLAMMABLE LIMITS IN AIR (Volume %): Not applicable

EXTINGUISHING MEDIA: Flood with water or carbon dioxide (CO2)

SPECIAL FIRE FIGHTING PROCEDURES: Use National Institute of Occupational Safety & Health (NIOSH) approved respirator with acid type canister or use self-contained breathing apparatus. Unusual fire and explosion hazards: material is a strong oxidizer. Contact with combustibles may initiate or promote combustion. Acid and heat accelerate decomposition. Decomposition products may include chlorine.

SECTION V - HEALTH HAZARD INFORMATION

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

No medical conditions are known to be aggravated by exposure.

ROUTES OF EXPOSURE

INHALATION: Fumes from spills can cause severe irritation and chemical burns to the nose, throat, and lungs. Very little hazard from properly stored solution.

SKIN CONTACT: Severe irritant, reddening of skin, can cause chemical burns to skin.

SKIN ABSORPTION: Same as skin contact.

EYE CONTACT: Severe irritant, corrosive, can severely burn eyes.

INGESTION: Causes irritation of membranes of the mouth, throat, and stomach pain and possible ulceration. LD50 (oral, rat) for 12.5% NaOCl is approximately 5 g/kg body weight.

EFFECTS OF OVEREXPOSURE

ACUTE OVEREXPOSURE (see Routes of Exposure above)

SWALLOWING: See "ingestion" under routes of exposure.

SKIN CONTACT: severe Irritant, reddening of skin, skin damage, chemical burns.

INHALATION: Fumes from spills are very irritating to mucous membranes.

EYE CONTACT: Extreme irritant, corrosive.

CHRONIC OVEREXPOSURE (see Routes of Exposure above)

EYE: Can cause damage.

SKIN: Can cause damage, chemical burns.

EMERGENCY AND FIRST AID PROCEDURES

IF ON SKIN OR CLOTHING: Take off contaminated clothing rinse skin immediately with plenty of water for 15-20 minutes; call a poison control center or doctor for treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes; remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye; call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call poison control center or doctor immediately for treatment advice; have person sip a glass of water if able to swallow, do not induce vomiting unless told to do so by the poison control center or doctor, do not give anything by mouth to an unconscious person.

IF INHALED: Move person to fresh air; if person is not breathing. call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible; call a poison control center or doctor for further treatment advice. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

SECTION VI - REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY

Solutions are fairly stable in concentrations below 10%. Stability decreases with concentration, heat, light, exposure, decrease in pH, and contamination with heavy metals, such as nickel, cobalt, copper, and iron.

INCOMPATIBILITY

Acids, alcohols, amines, ammonia, chlorinated isocyanurates, combustibles, cyanides, detergents, ethers, hydrocarbons, oxidizable materials, reducing

agents. Corrosive to most metals .

DECOMPOSITION PRODUCTS

Hypochlorous Acid (HOCl), chlorine, hydrochloric acid. Composition depends upon temperature and decrease in pH. Additional decomposition products, which depend upon pH, temperature and time, are sodium chloride, sodium chlorate and oxygen.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION

Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

IN THE EVENT OF A TRANSPORTATION EMERGENCY, CALL CHEMTREC: (800) 424-9300

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Cleanup personnel must wear proper protective equipment (See Section VIII). Contain in diked area. Neutralize with sodium bisulfite or ferrous salt solutions. Place neutralized material in DOT specification approved container(s). Flush area with large amounts of water. Comply with all Federal, State and Local reporting requirements.

WASTE DISPOSAL

Contact Federal, State, County, and Local environmental regulators for guidance regarding proper disposal .

RCRA: Test waste material for corrosivity, D002, prior to disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

VENTILATION REQUIREMENTS: Local exhaust is recommended.

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: Use National Institute of Occupational Safety and Health (NIOSH) or Mine Safety and Health Administration (MSHA) approved respirator appropriate for this product when permissible exposure limits are exceeded.

EYES: Use chemical goggles and face shield.

GLOVES: Use chemical resistant rubber, plastic, or neoprene gloves.

OTHER: Use chemical resistant splash apron and boots. Safety shower and eye wash fountain should be located nearby.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING

DANGER: This product is corrosive and may cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin or on clothing. Wear goggles and face shield and chemical resistant gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until odors have dissipated.

PROPER STORAGE AND DISPOSAL REQUIREMENTS

Store this product in a cool, dry area away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water.

Disposal for domestic use: Do not reuse container. Rinse thoroughly before discarding in trash. Disposal for all other uses: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Store in an upright position!!!

OTHER PRECAUTIONS

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with gross filth such as feces, urine, etc., or with ammonia, acids, detergents or other chemicals may release hazardous gases irritating to eyes, lungs and mucous membranes.

SECTION X REGULATORY STATUS INFORMATION

This product is listed in the Toxic Substances Control Act (TSCA) Inventory Of Chemical Substances.

Manufactured in Accordance with AWWA Standard for Hypochlorites, AWWA B300-99.

SARA Title III Extremely Hazardous Substance: No

SARA Title III Toxic Chemical: No

SARA 311/312:

Acute Hazard, Chronic Hazard, Fire Hazard, Reactivity Hazard

EPA CLEAN AIR ACT: This product does not contain nor is it manufactured with Ozone depleting substances.

Super fund Reportable Discharge = 100 pounds (100% NaOCl)

CERCLA Hazardous Material: Yes

California Proposition 65: No

For Additional Information:

Contact: MSDS Coordinator - Univar USA

During business hours, Pacific Time - (425) 889-3400

NOTICE

Univar USA expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a Product Specification Sheet and/or a Certificate of Analysis. These can be obtained from your local Univar USA Sales Office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar USA makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar USA's control. Therefore, users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes, and they assume all risks of their use, handling, and disposal of the product or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other material or in any other process.

END OF MSDS